READY MIXED WALLPAPER PASTE



Groovy Magnets wallpaper paste is a ready-to-use pasty wall covering adhesive for applying vinyl wall coverings with paper or textile backing.

SPECIFICATIE _____

Starch and synthetic resin based adhesive

Type of glue: pH 7.5

Processing time: 15 - 45 minuten Consumption: 150 - 300 g/m² *

* Consumption depends on the surface to be bonded. See paragraph 'Applying the glue'.

SUPPLIES -

How much alue do I need?

A 1 kg pot of ready-to-use wallpaper adhesive is more than enough for one strip of 120x265cm magnetic wallpaper.

Glue roller

Use a glue roller to spread the ready-to-use wallpaper adhesive for magnetic wallpaper evenly on your surface. The roller can be reused by rinsing it with warm water.

Pressure roller

Use a pressure roller to press your wallpaper firmly against the wall and to remove any air bubbles.

APPLYING THE GLUE _

Which underground?

Groovy Magnets wallpaper adhesive can be applied on almost any smooth indoor surface such as: smooth painted walls and doors, metal, wood, glass, cardboard, paper, plastic, kitchen cabinets,...

The surface should be even and clean. If necessary, smooth and sand down any bumps. Spread the adhesive directly onto the substrate with a glue roller. The wide surface of the roller ensures that the glue is evenly distributed. Be sure to use enough glue where the edges of the wallpaper will be. Do not worry if you have spilled some glue, you can remove it with a damp cloth and some washing-up liquid (do this immediately after application).

TIP: Glue one strip at a time. Mark the width of the strip with a pencil on the wall so you know where to apply the glue.

Pre-gluing?

If you aren't sure whether your surface is absorbent or not, **test by spraying water to the surface with a plant sprayer**. In case colour change appears within 3 mins: Pre-gluing is necessary.

Pre-gluing method:

Dilute the glue with up to max. 25% water and spread 1 layer of the mixture on the surface with a glue roller. When the surface feels dry (after about 15 min), start actual gluing for wallpapering.

STORAGE & MAINTENANCE _

How to store

Store the glue in the closed packaging preferably at room temperature. The shelf life of the product is 12 months.

Cleaning

Non-dried adhesive can be easily cleaned with water.

